

# Multifunction Shower Head

+ ShowerStart® TSV

evolve™



Make your hot water last longer while cleverly saving thousands of gallons a year.

This shower head's integrated ShowerStart TSV technology, elegant styling, high-nozzle-count spray patterns and high-pressure performance (regardless of your home's water pressure), forever changes the things that bother you most about showering. Enjoy more freedom, comfort and convenience - both before and during your shower.



More hot water for you.

About a minute's worth of hot water is accidentally wasted every time you start your shower. Save it and you'll have more hot water when you need it most.



Freedom while you wait.

Mornings are better when you don't have to choose between wasting your time or wasting your hot water. Now you can brush your teeth, shave or pick out the perfect outfit ... and your shower will just wait for you.



Alerts you when your shower is ready.

The first time you hear your shower slow to a trickle you'll feel the freedom of knowing it's warm and waiting.



No more empty showers running endlessly.

Frustrated with family members letting the shower run on and on while doing something else? Stop it when it's hot and save gallons of water every time they shower.



High pressure performance.

Because this shower head delivers a clean, powerful and comfortable spray regardless of your home's water pressure, it's sure to have you singing in the rain. Select the model that's right for you.






## How ShowerStart TSV Works




### 1 Turn on shower.

Cold water exits. Continue with your typical routine - the things you do while waiting for the shower to become warm.



### 2 ShowerStart® kicks in.

When the water reaches 95° F, ShowerStart automatically lowers the flow to a trickle - saving hot water until you're ready to get in.



### 3 Ready when you are.

You know your shower is warm, so pull the cord to resume full flow and begin showering.

## Multifunction Spray Patterns



Massage Spray



Full Body Spray



Pause Setting

## Physical Characteristics

- Integrated ShowerStart® TSV (Thermostatic Shut-off Valve) prevents hot water waste during shower warm up
- Designed for use in environments with static water pressures of 30 psi or higher
- Automatically resets for next use
- Full body spray, massage spray & pause
- 50 rub-clean, anti-clog spray nozzles
- Solid brass ½" NPT fittings (female)
- Plated ABS body
- Spray face diameter: 3.25" (83 mm)
- Length: 3.6" (91 mm)
- Weight: 9 oz (255 gm)
- 12" removable lanyard

## Specified Model

MODEL	DESCRIPTION	FINISH	SPRAY PATTERNS	FLOW RATE	PKG
EV3021-CP150-SB	Multifunction Showerhead + ShowerStart TSV	chrome	3	1.5 gpm (5.7 L/min)	single
EV3021-CP175-SB	Multifunction Showerhead + ShowerStart TSV	chrome	3	1.75 gpm (6.6 L/min)	single
EV3021-CP200-SB	Multifunction Showerhead + ShowerStart TSV	chrome	3	2.0 gpm (7.6 L/min)	single
EV3021-CP150-BP	Multifunction Showerhead + ShowerStart TSV	chrome	3	1.5 gpm (5.7 L/min)	bulk
EV3021-CP175-BP	Multifunction Showerhead + ShowerStart TSV	chrome	3	1.75 gpm (6.6 L/min)	bulk
EV3021-CP200-BP	Multifunction Showerhead + ShowerStart TSV	chrome	3	2.0 gpm (7.6 L/min)	bulk

©2018 Evolve Technologies LLC. All rights reserved.  
 Designed and developed in USA. Manufactured in China. Rev-0318  
 Patent <http://www.thinkevolve.com/patents>  
 Other U.S. and Foreign Patents Pending.

## Technical Notes

The ShowerStart TSV is not an anti-scald device:

- Lower water heater to a maximum of 120° F (49° C)
- Always resume water flow and check water temperature before entering shower
- Tankless systems require a minimum flow rate to produce hot water. When this product is used with some tankless systems a brief, yet noticeable, change in the shower's temperature may occur shortly after resuming the shower's normal flow

## 3 Year Warranty

## Codes / Standards

MEETS OR EXCEEDS THE FOLLOWING:

- Uniform Plumbing Codes (UPC): IAPMO IGC 244-2015a

