OVERVIEW

Simply Conserve® LED T8 Type A Lamps are an ideal plug-and-play replacement for 32W fluorescent tubes—delivering up to 2200 lumens while consuming less than half the power. Designed for ease of installation, the lamp features a durable glass construction that fits directly into existing fixtures without the need for rewiring or ballast bypass. Compatible with most electronic instant-start and programmed rapid-start T8 ballasts, this retrofit solution offers fast upgrades with bright, reliable performance. Perfect for commercial, industrial, and utility applications looking to reduce energy use without replacing entire fixtures.



FEATURES

- Plug-and-Play Installation
 Installs quickly with no rewiring—fits directly into most linear fluorescent fixtures using existing electronic ballasts.
- Long Life, Low Maintenance
 Rated for 50,000 hours of use, reducing the need for frequent replacements and lowering total cost of ownership.
- Smooth, Uniform Light Distribution
 Specialized cover design ensures flicker-free lighting with no dark spots or visual glare.
- Durable Glass Construction
 Provides excellent heat dissipation, structural strength, and a clean visual aesthetic.

· Reliable in a Range of Conditions

Suitable for enclosed fixtures and damp locations, with wide operating and storage temperature ranges (-4°F to 113°F operation; -40°F to 185°F storage).

True-to-Life Color

High CRI (≥80) delivers accurate color rendering in offices, retail spaces, and other visual environments.

· Safe and Low Emissions

Contains no UV or IR radiation and meets RoHS, DLC, and UL listing standards.



BEAM ANGLE



50,000 HOURS



TRUE COLOR



FLICKER-FREE



EASY TO INSTALL



DAMP-RATED

ORDERING INFORMATION

| SOURCE | LAMP WATTAGE | LAMP TYPE | MATERIAL | ССТ | OPERATION |
|---------|----------------------|--------------|-----------|------------|---------------|
| L = LED | 11 = 11W 14 = 14W | T8 = T8 Tube | G = Glass | 40 = 4000K | A = UL Type A |











LED T8 Type A





Savings Start Here™

SPECIFICATIONS

| MODEL # | LAMP WATTS | EFFICACY | ССТ | LUMENS | CRI | VOLTAGE | PF | HZ | DIM |
|----------------|------------|----------|-------|--------|-----|-----------------------|------|-------|-----|
| L11T8G40A-25PK | 11W | 163 lm/W | 4000K | 1800 | ≥80 | BALLAST- DEPENDENT | ≥0.9 | 50/60 | NO |
| L11T8G50A-25PK | 11W | 163 lm/W | 5000K | 1800 | ≥80 | BALLAST- DEPENDENT | ≥0.9 | 50/60 | NO |
| L14T8G40A | 14W | 157 lm/W | 4000K | 2000 | ≥80 | BALLAST- DEPENDENT | ≥0.9 | 50/60 | NO |
| L14T8G50A | 14W | 157 lm/W | 5000K | 2000 | ≥80 | BALLAST- DEPENDENT | ≥0.9 | 50/60 | NO |

DIMENSIONS





PRODUCT

| MODEL# | DIAMETER | L |
|----------------|----------|-----|
| L11T8G40A-25PK | 1" | 48" |
| L11T8G50A-25PK | 1" | 48" |
| L14T8G40A | 1" | 48" |
| L14T8G50A | 1" | 48" |

CASE

| MODEL# | L | w | н | GROSS WEIGHT | CASE QTY |
|----------------|-----|------|------|-----------------|-------------|
| L11T8G40A-25PK | 49" | 6.3" | 5.9" | 13 lbs. | 25 |
| L11T8G50A-25PK | 49" | 6.3" | 5.9" | 13 lbs. | 25 |
| L14T8G40A | 49" | 6.3" | 5.9" | 13 lbs. | 25 |
| L14T8G50A | 49" | 6.3" | 5.9" | 13 lbs. | 25 |

5-YEAR LIMITED WARRANTY



AM Conservation warrants that this product is free from defects in material and workmanship for a period of 5 years from the date of the first purchase or the original distribution of the product under an energy conservation program, subject to the proper installation and/or use of the product. For full standard limited product warranty, please visit amconservation.com/warranties.